




OIL WELL PUMP PARTS AND ACCESSORIES

PLUG, SEAT, API P12 (98)

(see notes)


| PUMP BORE | PART NUMBER | O.D. | THREAD SIZE | API NUMBER |
|-----------|-------------|--------|---------------|------------|
| 1-1/16" | 98B | 1.025" | 0.8750-14 | - |
| 1-1/4" | 98D | 1.188" | 1.0000-14 | P12-125 |
| 1-1/2" | 98F | 1.438" | 1.2500-14 | P12-150 |
| 1-3/4" | 98H | 1.688" | 1.4704-14 | P12-175 |
| 2" | 98K | 1.938" | 1.5604-14 | P12-200 |
| 2-1/4" | 98M* | 2.188" | 1.8024-14 | P12-225 |
| 2-1/2" | 98N* | 2.438" | 2.1095-11 1/2 | P12-250 |
| 2-3/4" | 98P* | 2.688" | 2.1095-11 1/2 | - |
| 3-1/4" | 98R* | 3.188" | 2.8000-11 1/2 | - |
| 3-3/4" | 98T* | 3.688" | 3.1715-11 1/2 | - |
| 5-1/2" | 98ZA* | 5.438" | 4.5000-8 | - |
| 4-3/4" | 98ZB* | 4.688" | 4.0000-10 | - |
| 7-3/4" | 98ZF* | 7.688" | 6.5000-8 | - |



PLUG, SEAT, RECESSED (98)

(see notes)

| PUMP BORE | PART NUMBER | HEX SIZE | THREAD SIZE |
|-----------|-------------|----------|-------------|
| 1-1/16" | 98B1 | 1/2" | 0.8750-14 |
| 1-1/4" | 98D1 | 9/16" | 1.0000-14 |
| 1-1/2" | 98F1 | 3/4" | 1.2500-14 |
| 1-3/4" | 98H1 | 7/8" | 1.4704-14 |
| 2" | 98K1 | 1" | 1.5604-14 |



Notes:

- A.) When ordering, indicate complete part number by adding:
 - 1.) The following prefixes to the base part number to indicate specific seat plug material:
 - Blank** - Carbon Steel
 - B** - Brass
 - S** - Stainless Steel
 - 2.) Adding suffix "**C**" to the base part number to indicate clutched seat plugs(*).
- B.) Clutched seat plugs are usually used in oversize rod/tubing pump configurations.